



HOSE FOR WATER / CHEMICALS

Dimensions

Length (mtr).....	3.0
Transport weight (kg).....	100
Weight per mtr (kg).....	31.56
Dimension (inch).....	10"
OD (mm).....	296.0
ID (mm).....	254.0

Type

Qty. available in stock.....	3
Fabricator.....	IVG Colbachini
Model.....	Bunkerflex ST / OSM 362
IKM Part number.....	BFX160FLE003
Suitable for.....	Chemicals, Oil, Water
Innercore.....	Black, smooth PVC/NBR rubber.
Steelcords.....	High strength synthetic cord plus antistatic copper wire and embedded steel helix.

Technical Specifications

Work pressure (bar).....	17
Work pressure (psi).....	255
Min. Temperature (GrC).....	-30
Max. Temperature (GrC).....	90
Bend radius (mm).....	1676
End couplings/fittings.....	10" 150# ANSI

Additional information

Equipment / Functions.....	Hose cover flame retardant according to ASTM C-542. Cover: black, smooth (wrapped finish), flame retardant CR rubber, resistant to weathering, abrasion, oil and sea water. Application: hardwall hose for suction and delivery of petroleum products with aromatic content up to 50% and drilling mud mixed with oil. Suitable as oil rig supply hose for service according IVG recommendations.
----------------------------	--