



## Zerust® AxxaClean™ 2048

Zerust®/Excor® AxxaClean™ 2048 is a fast-acting and non-hazardous\* rust and tarnish remover. It rapidly removes light to medium corrosion even in cracks and crevices. Cleaned surfaces are free of black-carbon residue and resistant to flash-corrosion.

Zerust®/Excor® AxxaClean™ 2048 cleans ferrous metals, brass, copper and various alloys of rust and tarnish. AxxaClean™ 2048 has a pH of about 2.5, similar to a soda drink, making it simple to use and minimizing disposal hassles. AxxaClean™ 2048 comes in multiple delivery forms; Immersion, Spray-On, and Brush-On. Cleaned and dried items can be immediately painted or welded. For optimum results with AxxaClean™ 2048, rinse cleaned items with a solution of AxxaVis™ PX-05AN acid neutralizer and dry thoroughly with filtered compressed air.

Surfaces treated with the rust remover are protected from flash-rust for several days in a controlled environment. To prevent the metal from corroding again protect it with Zerust® VCI packaging films and papers. For corrosion prone metals such as cast iron, use a Zerust® rust preventative such as Z-Maxx™, Axxanol™ or Axxatec™ liquid coating.

### Application Example

The thick viscosity of AxxaClean™ 2048 Brush-On product is easy to apply and clings to vertical surfaces, making rust removal quicker and with less mess.



### ► Benefits

Rapidly removes rust and tarnish

Inhibits flash corrosion on treated surfaces

No VOC's, CFC's, silicones or heavy metals

Compatible with most metals, painted surfaces, rubber and elastomers

Does not leave staining or dark carbon residues

Cleaned metals are ready to be painted or welded

### Complementary Products

Zerust® VCI Packaging and Diffusers  
Axxatec™ Water-Based RPs  
Axxanol™ Oil-Based RPs  
AxxaVis™ Additives  
AxxaWash™ Cleaners

\*Non-Hazardous Disposal: Product in unopened original container prior to use is non-hazardous waste in the United States according to 40 CFR 261 (no components listed on F, K, P or U lists; not ignitable, not corrosive, not reactive and not toxic).



## Technical Data

### Zerust®/Excor® AxxaClean™ Rust Remover Series Comparison

Attributes	AxxaClean ICT®620-RR	AxxaClean™ 2048	AxxaClean™ 3048
Corrosion Removal Power	Light to medium rust, even in cracks and crevices	Medium corrosion, even in cracks and crevices	Heavy corrosion, even in cracks and crevices
Speed	Slow	Moderate	Rapid
Metals Treated	Ferrous	Ferrous, brass, copper	Ferrous, brass, copper
Application Methods	Immersion	Immersion, Brush-on, Spray	Immersion, Brush-on
pH Level	Neutral pH of about 7	Mild acidic pH of about 2.5	Stronger acidic pH between 0.5-1.5
Temperature For Use	70°F (21°C) or above	70°F (21°C) or above	40°F (4°C) or above
Compatibility (<24 hour soak)	Safe for metals*, paint, gaskets, rubber, plastics	Safe for metals*, paint, gaskets, rubber, plastics	May attack soft metals*, some paints and coatings
Post-Cleaning Action	Do not let product dry on surface. Recommended DI or RO water rinse. Wipe off and dry well.	Do not let product dry on surface. Recommended DI or RO water rinse. Wipe off and dry well.	Do not let product dry on surface. Recommended DI or RO water rinse. Wipe off and dry well.
Corrosion Protection	Additional corrosion protection needed	Provides flash-corrosion protection in controlled environments	Provides flash-corrosion protection in controlled environments
Shelf Life and Handling	2 years from date of shipment when stored out of sunlight and in original packaging.	2 years from date of shipment when stored out of sunlight and in original packaging.	2 years from date of shipment when stored out of sunlight and in original packaging.

\*Test before use on zinc and cadmium. Check with your Zerust technical representative for details.

#### DECLARATION

This Data sheet and information it contains is considered to be accurate at the date of printing. No representation or warranty, expressed or implied is made as to the accuracy or completeness of the data and information contained in this publication. It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations.

#### LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on validations and tests conducted by Northern Technologies International Corporation/Zerust® or its partners and are believed to be reliable, but the accuracy or completeness thereof is not guaranteed. We warrant our products will be free from defects when shipped to customer. Our obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Northern Technologies International Corporation/Zerust® or its partners or agent of the claimed defect within 3 months after shipment of product to customer. Customer shall pay all freight charges for replacement products. We shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products. And any financial claims shall be limited to the value of the products sold.

Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of the company. The foregoing warranty is exclusive and in lieu of all other warranties, express, implied or statutory, including without limitation any implied warranty of merchantability or of fitness for a particular purpose. In no case shall Northern Technologies International Corporation/Zerust® be liable for incidental or consequential damages.

For full warranty and disclaimer information visit, [www.zerust.com/warranty](http://www.zerust.com/warranty).

©2013-2021 Northern Technologies International Corporation (NTIC). All Rights Reserved. NTIC is the owner of the following trademarks: ActivPak®, Cor Tab®, EXCOR®, Flange Saver®, ICT®, Natur-VCI®, NTI®, Plastab®, Z-CIS®, Zerion®, ZERUST®, 洁乐特, Z-PAK® and the Color "Yellow". ABRIGO®, UNICO®, and VALENO® are registered trademarks of EXCOR GmbH, a Joint Venture Partner of NTIC.

## ► Additional Info

Go online to [www.zerust.com](http://www.zerust.com) for product comparisons, application guides, videos and more.

## Contact a Zerust® Corrosion Expert

Consult a Zerust® representative to implement an optimum, cost-effective corrosion prevention system across your production facility and supply chain.

## ► Availability

Zerust®/Excor® AxxaClean™ 2048 is sold as a ready to use liquid product.

#### Part Number Sizes

##### Spray-On

350-M-00014 16 oz, 1, 5, 55 gal

##### Immersion

350-M-00015 16 oz, 1, 5, 55 gal

##### Brush-On

350-M-00016 16 oz, 1, 5, 55 gal

A product of:

Northern Technologies  
International Corp  
4201 Woodland Road  
Circle Pines, MN 55014  
USA

Phone. +1 763.225.6600  
Fax. +1 763.225.6645  
[sales@zerust.com](mailto:sales@zerust.com)  
[www.zerust.com](http://www.zerust.com)