

**IKM**

IKM Testing AS

Unit Nr. FU-52

OLJEFLUSHEUNIT

Onshore



Dimensjon	:	L 1550 mm	B 700 mm	H 1600 mm
Vekt	:	600 kg		
Løfting/Transport	:	Ramme med trucklommer.		

Tankvolum	:	350 l		
Q maks.	:	80 l/min.		
P maks.	:	200 bar		
Flowrate Q @ P 50 Hz	:	50 l/min @ 200 bar	70 l/min @ 150 bar	100 l/min @ 100 Bar
Viskositetsområde	:	10 - 160 cst. 1600 cst. ved oppstart.		
Tilkopling inn	:	1/2" BSP		
Tilkopling ut	:	1/2" BSP		
Anbefalt forankoplet sikring	:	63 A		
Spenningsområde	:	400 V	50 Hz	

Pumpe 1	:	Denison PV29 2RIC-C02			
Motor	:	MEZ KC180L04 512 H			
		230 VD	50 Hz	22 Kw	70A
		400 VY	50Hz	22 Kw	40A
		480 VY	60Hz	22 Kw	33A
Startskap	:	Industri			
		400 V	50Hz		
Filterhus tur	:	Finn Filter FF7007.F010.BS			
Filterhus retur	:	AL-I-HD3300-2D2C			
Filterhuselement tur	:	Finn Filter FC7007.F003.BK / D142G03A			
Filterhuselement retur	:	Finn Filter FC1302.Q020.BS / R432G03A			
Utstyr/Funksjoner	:	Prøve-uttak, Flowmeter, termometer og nivåglass			
Bygge år	:	1995			