



## BATTERY PACKAGE - POWERWALKER VFI 3000C LCD

### Dimensions

Length(mm).....: 640    Width(mm).....: 520    Height(mm).....: 380  
Weight (kg).....: 30

### Area of use / certification

Onshore/offshore.....: Onshore

### Type

Item type.....: Online Single Phase UPS  
Fabricator.....: BlueWalker GmbH  
Model.....: VFI 1000-3000 C LCD  
Serial no.....: S/N: 83322211501082

### Connections

Inlet connection.....: Input Voltage Range: 160-300 VAC  
Frequency (Synchronized Range): 47Hz -53Hz or 57Hz -63Hz  
Input Type: IEC C20 or IEC C20UK  
Outlet connection.....: Nominal Output Voltage: 200/208/220/230/240 VAC  
Voltage Regulation: +/-1%  
Frequency (Battery Mode): +/-0.3Hz  
Outlets: IEC C13 (4) + Terminal (1)

### Power supply

Battery.....: 6 x 12V/ 9Ah. (DC Voltage 6 x 12V)  
Storage / Memory.....: Full Load Backup Time: 4.5 min  
Half Load Backup Time: 13 min  
Recharge Time: 9h to 90%  
Transfer Time [AC to Battery]: 0ms  
Transfer Time [Inverter to Bypass]: 4ms

### Additional information

Equipment / Functions.....: The PowerWalkerVFI 3000C series provides powerful and overall protection to critical/sensitive applications, such as servers, network/telephone communication systems, and industrial applications. It offers the benefits of double conversion, like pure sine wave, stable output voltage, compatibility with generator and 0ms transfer time. It also features an external battery connector, and it is compatible with a SNMP Card for IT purposes and remote monitoring.

- Human Interface Device (HID) supported
- Ext. Battery Connector for EBM
- Includes an Intelligent Slot
- Comprehensive display allows easy monitoring and access of UPS status