



PARTIKKELTELLER

Dimensions

Length(mm).....: 582 Width(mm).....: 382 Height(mm).....: 340
 Weight (kg).....: 20
 Lifting/ Transportation.....: Custom transport box

Construction year

Built.....: 2023

Type

Fabricator.....: Pall
 Model.....: PCM500 X357
 Serial no.....: PCM S/N: 689
 Printer S/N: DIADELAHJ01268
 Fluid types.....: Water, glycol, water based and syntetic oil,
 This is a low viscosity PCM.
 This is primarily used on liquids up to 40 Centi stock.

Flow / Pressure / Volume

P-max (bar).....: 200
 Min. viscosity (cst).....: 1
 Max. Viscosity (cst).....: 40
 Minimum temp. (GrC).....: 10
 Max temp. (GrC).....: 80
 Measuring Range.....: 0,5 – 40 Viskositet / cSt

Connections

Inlet connection.....: 3x USB, Ethernet, RS232C

Power supply

El.Power1.....: 90-260 VAC (Hz).....
 Battery.....: 12VDC Lithium Ion

Additional information

Equipment / Functions.....: Contents:
 1 ea. PCM-500
 1 ea. Printer
 2 ea. Power supply / charger
 3 ea. Rolls with printer paper
 1 ea. Cable for printer
 1 ea. USB 32GB