

Technical datasheet

OTW.3C.300.6kW.130.SS316

OTS ID.: 7000-101

Introduction

The unit is driven by 400 V 16 amp with integrated frequency converter. The stainless steel pump is adjustable from 0-300 l/min.

The unit is designed with a tank volume up to 130 L. and is able to work with liquid temperatures from -20°C to +90°C. With the stainless steel design, the 3C unit is able to work with strong chemicals.

The unit is built ultra-compact and is easy to transport in a van or by aircraft.

The unit is designed with four-armed chain lifting point..

The unit is able to switch flow direction for reverse cleaning in the pipe system.



Features

- Adjustable flow from 0-300 L/min.
- Max. system pressure 5 bar.
- Tank capacity 130 L.
- Tank fitted for 4 x 25 Litres cans.
- SS1050 magnetic inset filter.

Capacity & performance

Electrical features:	400 V 50 Hz 16 amp 10kW
Adjustable Heater:	6 kW
Electric motor:	4 kW
Max/min liquid temp.:	-20/+90 °C
Max/min ambient temp.:	-20/+40 °C

Safety features

- All stainless steel design.
- Safety valve set at 5 bars pressure.
- Built-in driptray.
- Tank lid with drip tray.
- Variable thermostat up to 90°C

Weight & dimensions

Length	800 mm
Width	650 mm
Height	935 mm
Gross weight	240 Kg