

# UTILITY HOSE

WP 20 Bar R < 1 MEGA Ω ISO 8031 ref: 15X-xxx

## APPLICATION

Air/Water, Fuel/Oil, Nitrogen.

Standard: Exceeds BS 5118/1

Conductive R < 1 Mega Ω ISO 8031

Sizes: 1/4" to 10"

Working temperature range: -30 °C to +100 °C

Pressure: 20 Bar / 300 PSI

Hose Structure:

EPDM synthetic rubber, ozone and weather resistant.

Inside: Black conductive NBR synthetic rubber.

Reinforcement: High tension textile.

Universal hoses Yellow/Blue/Green/White

Yellow - 11155-xxx

Blue - 11156-xxx

Green - 11157-xxx

White - 11159-xxx



Part no	ID		OD (mm)	Working Pressure		Burst Pressure		MBR (m)	Weight (kg/m)
	(inch)	(mm)		(bar)	(psi)	(bar)	(psi)		
11155-006-A	1/4	6	13	20	300	60	900	30	0,17
11155-008-A	5/16	8	15	20	300	60	900	50	0,23
11155-010-A	3/8	10	17	20	300	60	900	60	0,28
11155-013-A	1/2	13	20	20	300	60	900	78	0,35
11155-019-A	3/4	19	28	20	300	60	900	114	0,61
11155-025-A	1	25	35	20	300	60	900	150	0,82
11155-032-A	1-1/4	32	42	20	300	60	900	190	1,26
11155-038-A	1-1/2	38	49	20	300	60	900	260	1,46
11155-051-A	2	51	63	20	300	60	900	350	1,56
11155-076-A	3	76	93	20	300	60	900	500	2,95
11155-089-A	3-1/2	89	107	20	300	60	900	580	3,64
11155-102-A	4	102	120	20	300	60	900	650	4,41
11155-127-A	5	127	146	20	300	60	900	800	5,39
11155-152-A	6	152	175	20	300	60	900	1000	7,55
11155-203-A	8	203	229	20	300	60	900	1500	11,49
11155-254-A	10	254	280	20	300	60	900	1800	14,19

BERGEN  
SJØKRIGSSKOLEVEIEN 15  
5165 LAKSEVÅG  
NORWAY

STAVANGER  
MOSEIDVEIEN 17  
4033 STAVANGER  
NORWAY