IKM Testing AS

Unit No. HJ-28

UNIT FOR HYDROJETTING

Dimension	:	W 2440 mm L 6050 mm H 2660 mm
Weight	:	9400 kg
Lifting/Transport	:	20" container with lifting slings and forklift channels.

Water supply	:	Via pulsation dampener with a 2-7 bar feed-water pressure.	
Volume diesel tank	:	600 l	
Conversion	:	**Standard pumphead:**	**Alternative pumphead:**
Q max.	:	188 l/min.	600 l/min
P max.	:	1000 bar	300 bar
Connection in	:	2" fire coupling / Nor lock 1	
Connection out	:	M36	
Recom. back up fuse	:	Light and stings: 16A Light and stings: 230V 50-60 Hz	
Voltage range	:	24 VDC	

Pump	:	Kamat K 35036A	Ser. no. 147728
Motor	:	Scania DC1643 Type: A02P	Ser. no. 6506585
Filter feed water	:	Washable strainer	
Air/Diesel supply shut down if	:	- Low oil pressure on pump. - High temperature on motor. - Low oil pressure on motor. - Emergency shut-down. - Feed-water pressure under 2 bar.	
Equipment/Functions	:	Remote control of pump, PSV	
Other information	:	Pump with reduction gear and air operated clutch. Heater and lights	
Diesel consumption at full effect	:	100 l/hour	
Built	:	2005 / Built in container 2019	