



Unit No. SK4-2-01

HYDRAULIC TORQUE WRENCH - HYDRATIGHT SWEENEY

Dimensions

Length(mm).....: 204 Width(mm).....: 35 Height(mm).....: 151
Weight (kg).....: 0
Equipment Weight - (kg): 2

Type

Item type.....: Hydraulic torque wrench - HEX
Fabricator.....: Hydratight (Sweeney)
Model.....: Torque wrench RSL4, 2" (50 mm) (to be connected to Power Head 4)
Qty. available in stock.: 4

Technical information

P-max (bar).....: 690 P-max (PSI)...: 10000
Torque min. (Nm).....: 393
Torque max. (Nm).....: 4176

Connections

Inlet connection.....: Twin hose

Additional information

Equipment / Functions...: Dimensions (LxWxH) are for complete tool (Power Head and HEX drive)

Safe

- Innovative design that completely encloses all moving parts and eliminates pinch points

Fast

- 30 – 35 degrees of operating stroke provides added productivity while avoiding “tool lock on” which is common with some torque wrench designs
- Versatile
- Interchangeable head design
- Power head / square drive combination for flexible use with standard impact quality sockets
- Power head / hex head combination for limited height in line solutions
- Wide range of hex sizes available for all applications
- 360 degree movement of reaction arm with simple dial lock for rapid change
- For use topside and subsea

Compact

- Designed to give optimum strength to weight and torque to weight ratios
- Minimum nose radius for trouble-free tool fit