IKM Testing AS

Unit No. HHD-21

Hosedrum
for CTS disposal hose

Lifting in acc. to DNV 2.7-1

Dimension	:	L 2650 mm	W 2700 mm	H 2820 mm
Weight	:	2900 Kg, MGW 7000 kg		
Lifting/Transport	:	Frame with forkliftchannels and slings.		
Ref. cert./Ser. no. frame	:	HHD-21		

Hydraulic	:	200 Bar
Recommended Flow	:	Min 40 liter - Max 300 liter
Max pressure in	:	350 Bar
Min pressure in	:	200 Bar
Hydraulic inlet coupling	:	¾" Tema 7511 Quick connection Female
Hydraulic outlet coupling	:	¾" Tema 7521 Quick connection Male
Hydraulic leak coupling	:	½" Tema 5011 Quick connection Female

Hydraulisk motor	:	Ser. Nr:
		Approx. 30 kW. 800 Nm at 200 Bar oil supplied
Traction first layer	:	2,3 T w/200 bar pressure
Inner diameter, drum	:	1200 mm
Outer diameter, drum	:	2400 mm
With drum	:	1510 mm
Innerdiam. hose	:	241 mm
Spool speed	:	
Brake	:	Hydraulic brake
Equipment/Functions	:	Hyfraulic directional valve
Number of chambers in the drum	:	2
Other information	:	Can be driven by external HPU or rigg supply. Three-way-valve: Rigg supply or FU supply.
Built	:	Modified 2012