



SUBMERSIBLE PUMP

Dimensions

Length(mm).....: 360 Width(mm).....: 360 Height(mm).....: 850
Weight (kg).....: 90
Lifting/ Transportation.....: Lifted by hook / handle grip

Construction year

Built.....: 2004

Area of use / certification

Onshore/offshore.....: Offshore

Type

Fabricator.....: ITT Flygt
Model.....: 2125
Serial no.....: 181-0430042

Flow / Pressure / Volume

Hz v Q-max measure.....: 60 Q-max (l/min).....: 1176
Hz v P-max measure.....: 60 P-max (bar).....: 7.3

Connections

Inlet connection.....: Suction through pump casing
Outlet connection.....: 1 ea 2" Camlock Female

Power supply

Fuse (A).....: 32
El.Power1.....: 400 V (Hz).....: 50 (kW).....: 9,7 (A).....: 12,5
El.Power2.....: 440-480 V (Hz).....: 60 (kW).....: 9,7 (A).....:
Starter.....: CEAG GHG 635 1101 R0112
12,5-16,0A

Additional information

Equipment / Functions.....: Delivered with a 35 m cable and 50 m cable to the enclosure.

Max pre-connected protection : 100 A/60 (ICS) @ 400V 100A/25KA(ICS) @ 500V