



## DOUBLE BLOCK AND BLEED PLUG

### Dimensions

Equipment Weight - (kg).....: 11  
Lifting/ Transportation.....: Transportation on pallet

### Construction year

Built.....: 2017

### Area of use / certification

Onshore/offshore.....: Offshore

### Type

Item type.....: Double block and bleed plug  
Fabricator.....: Curtiss Wright  
Model.....: DBB-6P10

### Flow / Pressure / Volume

P-max (bar).....: 155	P-max (PSI).....: 2250
Max Upstream pressure (bar).....: 0.7	
Nominal Pipe Size (Inches).....: 6.00	
Nominal Pipe Schedule.....: 10	
Plug Outside Ø (mm).....: 156.5	
Clearance with pipe (mm).....: 5.1	
Plug Length (mm).....: 229	

### Additional information

Equipment / Functions.....: Distance Between Seals : 101,6 mm

Installation:  
Normal Installation Torque : 122 Nm  
Maximum Installation Torque : 190 Nm  
Hex Nut Wrench Size: 1 1/16"

The Double Block and Bleed (DBB) plug revolutionizes isolation and testing of pipe connections. The DBB plug allows an operator to positively isolate and monitor potentially explosive vapors during "hot work", then effectively hydrotest the new weld system connection with one easy to use tool. The aluminium/steel construction makes the tool highly portable and easy to position. The volume of water required for a test is so small that testing can be accomplished using a hand pump. This greatly facilitates testing in remote areas of the facility.

#### Features

- Safely isolate hot work from any residual upstream gases
- Positive pressure barrier created between the seals
- Dual port system can circulate water (or other media) between seals, providing increased cooling capabilities during pre/post weld procedures
- Lightweight aluminum and steel construction - easy to maneuver
- Reduces fill times