Unit no. MP-203

IKM Testing AS

DIAPHRAGM PUMP

Dimensions

Length(mm).....: 640 Width(mm).....: 500 Height(mm).....: 1050
Weight (kg).....: 73
Lifting/ Transportation.....: Mounted in Frame. Transportation on pallet

Construction year

Upgraded/rebuilt.....: 2022

Area of use / certification

Onshore/offshore.....: Offshore
Standard.....: EX/Atex, CE, Norsok, Zone 1

Type

Fabricator.....: RAASM
Model.....: AAB-2-N-580
Serial no.....: 090500004-2022 (Art no. 3C6/5066VNHH)

Flow / Pressure / Volume

Q-max (l/min).....: 500
P-max (bar).....: 8 P-max (PSI).....: 115
Flowrate1.....: 580 ltr/min @ 1 bar
Flowrate2.....: 320 ltr/min @ 4 bar
Flowrate3.....: 100 ltr/min @ 7 bar
Max temp. (GrC).....: 82

Connections

Inlet connection.....: 2” Camlock Male
Outlet connection.....: 2” Camlock Female
Air connection.....: 1" offshore claw coupling
Air supply (P@Q).....: Max 6,7 bar

Additional information

Equipment / Functions.....: Max suction, dry : 5 metres
Max suction, wet: 7,5 metres

Max particle size: 6,5mm

Pressure regulator on airsupply to regulate flow / pressure.