



PUMP FOR PIGGING / CHEMICAL CLEANING

Dimensions

Length(mm).....: 2000 Width(mm).....: 1400 Height(mm).....: 1620
 Weight (kg).....: 1200
 Lifting/ Transportation.....: Frame with forklift channels. Frame, slings and shackles in acc. to Machinery regulations 522
 Ref. cert./Ser. no. frame : SLFP-4-15-1300

Construction year

Built.....: 1992

Area of use / certification

Onshore/offshore.....: Onshore
 Power (Electrical/Diesel).....: Electrical

Flow / Pressure / Volume

Hz v Q-max measure.....: 50 Q-max (l/min).....: 1300
 Hz v P-max measure.....: 50 P-max (bar).....: 15

Connections

Inlet connection.....: 1 ea. 4" 150# RF flange
 Outlet connection.....: 1 ea. 2" Camlock Male (mounted in 2" 150# RF)

Pump(s)

Pump1 (type).....: Robuschi Keminor R50-315
 Pump1 (Cert. No.).....: 9120496

Motor / Engine(s)

Motor1 (type).....: ATB DE250M
 Motor1 (Cert. No.).....: XP111147-01

Power supply

Fuse (qty).....: 1	Fuse (A).....: 125		
EI.Power1.....: 380 VD	(Hz).....: 50	(kW).....: 55	(A).....: 100
EI.Power2.....: 440 VD	(Hz).....: 60	(kW).....: 64	(A).....: 101
Starter.....: Industrial, 400-440 V Max. load 100 A 50-60 Hz			

Additional information

Equipment / Functions.....: Pump in acid-resistant material.