**Unit no. PP-25**

IKM Testing AS

# PUMP FOR PIGGING / CHEMICAL CLEANING

## *Dimensions*

Length(mm).....: 5000 Width(mm).....: 2250 Height(mm).....: 2500
Weight (kg).....: 9000
Lifting/ Transportation.....: Frame with forklift channels and lifting device. DNV 2.7-1
Ref.cert. / Ser. no. frame : 1047.05

## *Construction year*

Built.....: 2005

## *Area of use / certification*

Onshore/offshore.....: Onshore
Standard.....: 102 dBA
Power (Electrical/Diesel).....: Diesel

## *Flow / Pressure / Volume*

Hz v Q-max measure.....: N/A (Diesel)
Hz v P-max measure.....: N/A (Diesel)
Flowrate1.....: 13000 ltr/min @ 5 bar
Flowrate2.....: 10000 ltr/min @ 6 bar
Flowrate3.....: 4300 ltr/min @ 7 bar

Q-max (l/min).....: 13000
P-max (bar).....: 7

## *Connections*

Inlet connection.....: 10” 150# RF
Outlet connection.....: 8” 150# RF

## *Pump(s)*

Pump1 (type).....: Godwin HL250M Dri Prime
Pump1 (Cert. No.).....: 0539022/03 P:V

## *Motor / Engine(s)*

Motor1 (type).....: Caterpillar diesel Mod.3406 220 HK
Motor1 (Cert. No.).....: 3ER08839 130-4571

## *Power supply*

Starter.....: Electrical 24VDC

## *Flow / Pressure / Volume*

Diesel consumption (ltr/hr).....: 100

## *Additional information*

Equipment / Functions.....: - Fire extinguisher 12kg.
- Max suction height ejector 7,5 meters.