



HYDRAULIC TORQUE WRENCH - HYDRATIGHT SWEENEY

Dimensions

Length(mm).....	305	Width(mm).....	64	Height(mm).....	230
Equipment Weight - (kg).....	3				

Type

Item type.....	Hydraulic torque wrench - HEX
Fabricator.....	Hydratight (Sweeney)
Model.....	Torque wrench RSL14, 4-1/4" (108 mm) (to be connected to Power Head 14)
Qty. available in stock.....	8

Flow / Pressure / Volume

P-max (bar).....	690	P-max (PSI).....	10000
Torque min. (Nm).....	1302		
Torque max. (Nm).....	15123		

Connections

Inlet connection.....	Twin hose
-----------------------	-----------

Additional information

Equipment / Functions.....	Dimensions (LxWxH) are for complete tool (Power Head and Square drive)
----------------------------	--

Safe

- Innovative design that completely encloses all moving parts and eliminates pinch points

Fast

- 30 – 35 degrees of operating stroke provides added productivity while avoiding “tool lock on” which is common with some torque wrench designs
- Versatile
- Interchangeable head design
- Power head / square drive combination for flexible use with standard impact quality sockets
- Power head / hex head combination for limited height in line solutions
- Wide range of hex sizes available for all applications
- 360 degree movement of reaction arm with simple dial lock for rapid change
- For use topside and subsea

Compact

- Designed to give optimum strength to weight and torque to weight ratios
- Minimum nose radius for trouble-free tool fit