



## SWEENEY KASSETT 6 - 3 1/8"

### Dimensions

Length(mm).....: 247  
Equipment Weight - (kg).....: 2  
Width(mm).....: 45  
Height(mm).....: 183

### Type

Item type.....: Hydraulic torque wrench - HEX  
Fabricator.....: Hydratight (Sweeney)  
Model.....: Torque wrench RSL6, 3-1/8" (80 mm) (to be connected to Power Head 6)  
Qty. available in stock.....: 8

### Flow / Pressure / Volume

P-max (bar).....: 690  
Torque min. (Nm).....: 619  
Torque max. (Nm).....: 7190  
Nut Size.....: 080 mm - (3 1/8")  
P-max (PSI).....: 10000

### Connections

Inlet connection.....: Twin hose

### Additional information

Equipment / Functions.....: Dimensions (LxWxH) are for complete tool (Power Head and HEX drive)

#### Safe

- Innovative design that completely encloses all moving parts and eliminates pinch points

#### Fast

- 30 – 35 degrees of operating stroke provides added productivity while avoiding "tool lock on" which is common with some torque wrench designs
- Versatile
- Interchangeable head design
- Power head / square drive combination for flexible use with standard impact quality sockets
- Power head / hex head combination for limited height in line solutions
- Wide range of hex sizes available for all applications
- 360 degree movement of reaction arm with simple dial lock for rapid change
- For use topside and subsea

#### Compact

- Designed to give optimum strength to weight and torque to weight ratios
- Minimum nose radius for trouble-free tool fit