



HOT WATER CLEANER

Dimensions

Length(mm): 2160 Width(mm): 900 Height(mm): 1600
Weight (kg): 1200
Lifting/ Transportation: Frame with forklift channels and lifting slings. DNV 2.7-1
Certificate(s) / Serial No: SU-10

Construction year

Built: 1998
Upgraded/rebuilt: 2022

Area of use / certification

Onshore/offshore: Offshore
Standard: Eexde IIB T4 Zone 1, Norsok Z-015

Flow / Pressure / Volume

Feed water tank volume (ltr): 380
Jetting-lances (Qty): 1
Q-max (l/min): 21
P-max (bar): 270 P-max (PSI): 3916
Max temp. (GrC): 65

Connections

Inlet connection: 1" Offshore claw coupling
Outlet connection: Flushing lance

Filter

Inlet filter house (type): SPECTRUM INOX SFH-SBR-1-10-3/4
Inlet filter element (type): 1 stk. Stavfilter PX2010 +Strainer, 93719-16 i tanken

Pump(s)

Pump1 (type): Hawk XLT1830IEXR
Pump1 (Cert. No.): 10014

Motor / Engine(s)

Motor1 (type): Teve Varnost 4KTC 160L-4
II 2 G Ex db eb IIC T4 Gb IP56
BVS 13 ATEX E 125 X
Motor1 (Cert. No.): 202203248

Power supply

Fuse (qty): 1 Fuse (A): 63
El.Power1: 380-415 VD (Hz): 50 (kW): 11 (A): 22
El.Power2: 690 VY (Hz): 50 (kW): 11
El.Power3: 380-415 VD (Hz): 60 (kW): 11
El.Power4: 440-480 VD (Hz): 60 (kW): 12,9
El.Power5: 660-690 VY (Hz): 60 (kW): 11 (A): 12,1
Heater: 2stk Cetal TPAE 115d
Eexd IIC T6, 400-690 V 50-60 Hz
II2D EX D IIC T4 GB
LCIE 07 ATEX 6004 X

Unit no. SU-10



Starter.....: MES type 21-013
400-690 V Max. load: 63 A 50-60 Hz
II2G (1) G Ex db eb [ia Ga] IIC T4 Gb
Snr 2200110-001
DNV 21 ATEX 14904 X

Additional information

Equipment / Functions.....: Q max / P max above are for 60 Hz. Q max 50 Hz: 17 ltr/min, P max 50 Hz: 270 bar

Delivered with a 25 meter 3/8" hose and flushing lance.

Manhole cover in tank, levelguard