



VIDEO INSPECTION CAMERA SYSTEM

Dimensions

Length(mm).....:	770	Width(mm).....:	550	Height(mm).....:	310
Weight (kg).....:	41				
Lifting/ Transportation.....:	5 ea packages				

Area of use / certification

Onshore/offshore.....: Onshore

Type

Item type.....: Video inspection Tractor. Vertical and Horizontal inspection
 Model.....: Control unit: VSR 55 / Camera: DTR 65HREX / Tractor: VSCE 200EX

Flow / Pressure / Volume

Range of use - Minimum (Ø mm)....: 100.0
 Range of use - Max recom.(Ø mm): 700.0
 Range of use - Length (m).....: 200
 Waterproof.....: yes
 Waterproof (bar).....: 5

Connections

Inlet connection.....: BNC
 Outlet connection.....: BNC

Power supply

El.Power1.....: 220-240 V AC 5 (Hz).....: 50-60 (kW).....: (A).....:

Additional information

Equipment / Functions.....: Packages:

- A: L 770 mm W 550 mm H 310 mm 41 Kg (19", Rack Control unit)
- B: L 630 mm W 500 mm H 355 mm 33 Kg (Pelicase 1620, Tractor)
- C: L 800 mm W 600 mm H 600 mm 88 Kg (Aluminium box, 200 Metres Electrical Winch)
- D: L 500 mm W 130 mm H 400 mm 8 Kg (Pelicase 1490, Laptop with software)
- E: L 630 mm W 500 mm H 355 mm 14 Kg (Pelicase 1620, Vertical Insp. Camera 30 Metres)

Range of use:
 NON-EX
 Horizontal: 6" - 30" 200 Metre length
 Vertical: 4" - 15" 30 Metre length
 Pan 360° and tilt 110°

Waterproof:
 Camera is waterproof down to: 50 Metres (5 Bar)
 Tractor is waterproof down to: 5 Metres (0,5 Bar)
 Extralight is waterproof down to: 100 Metres (10 Bar)