Unit no. VIP-19

IKM Testing AS

VIDEO INSPECTION PROBE

Dimensions

Length(mm).....: 570 Width(mm).....: 260 Height(mm).....: 750
Weight - (kg).....: 20
Lifting/ Transportation.....: Delivered in a hard-plastic transport case. See below for dimensions for all 3 kolli

Construction year

Built.....: 2006

Area of use / certification

Onshore/offshore.....: Offshore
Standard.....: Non EX/Atex

Type

Fabricator.....: Everest VIT
Model.....: XL INDUSTRIAL PRO+

Flow / Pressure / Volume

Range of use - Minimum (Ø mm)....: 6.0
Range of use - Max recom.(Ø mm).: 50.0
Camera diametre (mm).....: 6.0
Range of use - Length (m).....: 18.0
Waterproof.....: Yes
Waterproof (bar).....: 1

Connections

Inlet connection.....: BNC/S-Video, PC-keyboard for text-generator.
Outlet connection.....: BNC/S-Video, audio output (Phono).

Power supply

El.Power1.....: 100-240 V (Hz).....: 50-500 (kW).....:
Storage / Memory.....: 32 MB Internal Flash Memory up to 140 images (JPG/BMP)

Additional information

Equipment / Functions.....: VIP-19A : L: 570 mm W: 260 mm H: 750 mm 20 Kg
VIP-19B : L: 550 mm W: 500 mm H: 250 mm 7 Kg
VIP-19C : L: 500 mm W: 500 mm H: 150 mm 6 Kg

- 18 and 3 m operating length.
- 80º visual angle (depending on tip adapter)
- The tip is movable 110º in all directions. (3m)
- The tip is movable 90º in 2 way (18m)
- Operated by a hand-held piece with joystick.
- Video display in colours.
- 2 GB CF-card. (Up to 184 min. recording on CF-card)
- CF-card reader
- Integrated microphone.
- 3 x digital zoom.
- Comparison measurement (requires a known size in the image)
- Audio recording.
- Long exposure control.
- Manual focus.
- Text-generator.
- 18m probe requires shop air (120psi min) Hansen coupling