Unit no. VV-32

IKM Testing AS

HEAT EXCHANGER - AIR. 230v/ 16A unit

Dimensions

Length(mm).....: 2000 Width(mm).....: 1000 Height(mm).....: 2000
Weight (kg).....: 1000
Lifting/ Transportation.....: Mounted in frame with forklift channels

Construction year

Built.....: 2006

Area of use / certification

Onshore/offshore.....: Offshore
Standard.....: Z-015 type U99, Zone 1, ATEX II2G EEx dem IIC T4

Type

Fabricator.....: Vahterus
Model.....: PSHE 4HH – 102/1/1
Serial no.....: 18605

Flow / Pressure / Volume

Q-max (l/min).....: 25800
P-max (bar).....: 16
Max temp. (GrC).....: 250
Material Quality.....: Heat exchanger: acid-resistant material. Steam: carbon material.

Connections

Inlet connection.....: 2” Boss Dixon Steam Coupling (Exchanger)
8" 150# RF (Media)
Outlet connection.....: 2” Boss Dixon Steam Coupling (Exchanger)
8" 150# RF (Media)

Additional information

Equipment / Functions.....: - Q-MAX IS GIVEN WITH AIR.

- Capasity : 658 Kw
- Automatic regulation of temperature up to 80˚C