Unit no. TP-335

IKM Testing AS

TEST PUMP SC10-5-000S650-HF4

Dimensions

Length(mm).....: 600 Width(mm).....: 400 Height(mm).....: 600
Weight (kg).....: 25
Lifting/ Transportation.....: Two packages. Transportation on pallet

Construction year

Built.....: 2012

Area of use / certification

Onshore/offshore.....: Offshore
Standard.....: Non ATEX

Type

Fabricator.....: Hydratron
Model.....: HPU-SC10-6000S402

Flow / Pressure / Volume

Tank Volume (ltr).....: 5
P-max (bar).....: 4114 P-max (PSI).....:

Connections

Inlet connection.....: 1 ea 1" Offshore claw coupling
Outlet connection.....: 1 ea 1/4" HP Female
Air connection.....: 1 ea 1" Offshore claw coupling

Filter

Inlet Filter.....: Washable strainer

Additional information

Equipment / Functions.....: Dim transportation box A : L 600 mm / W 400 mm / H 600 mm (25 kg)
Dim transportation box B : L 600 mm / W 400 mm / H 600 mm (25 kg)

Content:
1 ea. PSV, inlet 9/16" HP, Female – SET 3998 Bar
1 ea. Transmitter 0-5000 bar (out: 4-20 m A) M16x1,5 Female
1 ea. X-OVER M16 x 1,5 male X 1/4" HP (for transmitter)
6 ea. Test hose, 3998 bar à10 mtr, 9/16" AE
5 ea. X-OVER 1/4" HP male X 9/16" HP male (60-21HM4HM9)
5 ea. 9/16" HP muff (60-21HF9)
1 ea. Manifold 4 X 1/4" HP female (TM60K-33)

Can be used with water, hydraulic and some type of chemicals.
Can be delivered with extra 60 litre tank and stroke -counte r.
Pressure transmitter must be calibrated prior to mobilisation. Estimated duration 1 week