



DISPOSAL HOSE REEL (CTS)

Dimensions

Length(mm).....:	2650	Width(mm).....:	2700	Height(mm).....:	2820
Weight (kg).....:	2900				
Lifting/ Transportation.....:	Frame with forklift channels and slings. DNV 2.7-1 MGW 7000 kg				
Certificate(s) / Serial No:.....:	HHD-35				

Construction year

Built.....: 2012

Area of use / certification

Onshore/offshore.....: Offshore

Flow / Pressure / Volume

Q-minimum (l/min).....:	40
Q-max (l/min).....:	300
Minimum Inlet pressure (bar).....:	200
Max Inlet pressure (bar).....:	350
Inner diameter drum (mm).....:	1200
Outer diameter drum (mm).....:	2400
Width drum (mm).....:	1510
Max pull-in force (inner layer).....:	2,3 T @ 200 bar pressure
Brake.....:	Hydraulic brake

Connections

Inlet connection.....:	Hose: 10" 150# ¾" Tema 7511 Quick connection Female
Outlet connection.....:	Hose: 10" 150# ¾" Tema 7521 Quick connection Male ½" Tema 5011 Quick connection Female

Motor / Engine(s)

Motor1 (type).....: Approx. 30 kW. 800 Nm at 200 Bar oil supplied

Additional information

Equipment / Functions.....: - Hydraulic directional valve
- 2 chambers in the drum

Can be driven by external HPU or rig supply.
Three-way-valve: Rigg supply or FU supply.