



HELIUM LEAK DETECTOR

Dimensions

Length(mm).....: 600 Width(mm).....: 485 Height(mm).....: 225
 Weight (kg).....: 12
 Lifting/ Transportation.....: Custom made suitcase/boxes
 A: L 600mm - W 485mm - H 225mm - (12 kg)
 B: L 460 mm - W 370mm - H 114mm - (2,6 kg)

Type

Type (HL).....: Hand-Held Leak detection (N2/He)

Area of use / certification

Standard.....: EN 61010-1
 EN 50270
 EN 61000-6-2
 EN 61000-6-3

Type

Item type.....: Hand-held helium leak detector
 Fabricator.....: Varian
 Model.....: PHD-4
 Serial no.....: Varian PHD-4 (Ser. No: IT15404006)
 Procal (Ser. No: 3322)

Flow / Pressure / Volume

Min. Detectable leak.....: 5 x 10-6 mbar l/sec. He
 Delay time.....: 2 second

Connections

Outlet connection.....: RS-232, headset

Power supply

Battery.....: Charger: 100-240 Vac 50/60 Hz 1 A
 Battery: NI-MH GP Cells, 12V 4500 MAH

Content

Content.....: PHD-4:
 3 ea Batteries,
 Travel case,
 Probe set,
 Carrying bag,
 Power cord and adapter.
 Procal:
 2 ea balloons,
 Power cable.