



Equipment / Functions.....: Frequency controlled pump, Pressure gauge, Pressure control valve, PSV.  
Unit is available with 3 different plunger set, please advise with your order which plunger sets to be alert settings.

PLUNGER ALTERNATIVE 2 - KT13036 (specify with order)  
Q max: 150 ltr/min  
P max: 400 bar  
P@Q: 150 ltr/min@205 bar, 100 ltr/min@310 bar, 50 ltr/min@390 bar  
Connection out: 1 ea M36 Ermeto Male

PLUNGER ALTERNATIVE 3 - KT13065 (specify with order)  
Q max: 496 ltr/min  
P max: 115 bar  
P@Q: 496 ltr/min@60 bar, 345 ltr/min@90 bar, 270 ltr/min@115 bar  
Connection out: 1 ea 2" BSP Male

- Max fluid temperature: 60°C
- Alarm : Gas, Phase sequence.
- Filter intake : Amazon Filters LTD Model 84012UAN30A1EV (Ser No. 39488)
- Filter element : Bag filter G2P5

Power Supply:  
- Cable size Main power: 4 G 35 mm<sup>2</sup> H07RN-F / 3 G 2,5 mm<sup>2</sup> H07RN-F  
- Overpressure fan, gas: 16 A, 230V 50/60 Hz