



## HYDRAULIC TORQUE WRENCH - HYDRATIGHT SWEENEY

### Dimensions

Length(mm).....	536	Width(mm).....	169	Height(mm).....	263
Equipment Weight - (kg).....	17				

### Type

Item type.....	Hydraulic Square drive torque wrench
Fabricator.....	Hydratight (Sweeney)
Model.....	Torque wrench RSL30 (to be connected to Power Head 30)
Qty. available in stock.....	2

### Flow / Pressure / Volume

P-max (bar).....	690	P-max (PSI).....	10000
Torque min. (Nm).....	3115		
Torque max. (Nm).....	37965		

### Connections

Inlet connection.....	Twin hose
-----------------------	-----------

### Additional information

Equipment / Functions.....	2 1/2" Square Drive
----------------------------	---------------------

Dimensions (LxWxH) are for complete tool (Power Head and Square drive)

#### Safe

- Innovative design that completely encloses all moving parts and eliminates pinch points

#### Fast

- 30 – 35 degrees of operating stroke provides added productivity while avoiding "tool lock on" which is common with some torque wrench designs
- Versatile
- Interchangeable head design
- Power head / square drive combination for flexible use with standard impact quality sockets
- Power head / hex head combination for limited height in line solutions
- Wide range of hex sizes available for all applications
- 360 degree movement of reaction arm with simple dial lock for rapid change
- For use topside and subsea

#### Compact

- Designed to give optimum strength to weight and torque to weight ratios
- Minimum nose radius for trouble-free tool fit