



## LINE BORING MACHINE

### Dimensions

Length(mm).....:	1250	Width(mm).....:	800	Height(mm).....:	720
Weight (kg).....:	230				
Equipment Weight - (kg).....:	201				
Lifting/ Transportation.....:	Shipped in 2 containers				

### Area of use / certification

Onshore/offshore.....: Offshore

### Type

Item type.....:	Electrical driven line boring machine
Fabricator.....:	Climax
Model.....:	BB5000
Serial no.....:	12711

### Flow / Pressure / Volume

Minimum bar length (mm).....:	1219.2
Max bar length (mm).....:	7315.2
Minimum drill hole Ø (mm).....:	38.1
Max drill hole Ø (mm).....:	304.8

### Power supply

Power (Electrical/Hydraulic).....: Electrical

### Additional information

Equipment / Functions.....: Machine: L 1334mm x W 686mm x H 419mm  
Bar: L 1892mm x W 165mm x H 178mm

Optional tool head for boring diameter up to 609,6mm has to be ordered at accessories.

Power supply : Electric 230V 16A  
Mounting Options: Single Arm, Double Arm, Universal, ID  
Rotational Drive Unit 4:1 gear ratio reduction

Machine can be used for line boring, drilling, facing, conventiocal boring and grooving.

#### Quick and Easy Setup

- Modular components make setup quick and easy.
- Fast and easy setup using high quality cast-iron set-up cones and spherical bearing mounts.
- Patented spherical bearing mounting system allows quick setup, with up to 5° of bearing misalignment.
- Typical set-up time for an experienced operator is 30 minutes or less.