



## MILLING MACHINE

#### **Dimensions**

### Area of use / certification

Onshore/offshore...... Offshore

## **Type**

 Item type
 Key mill

 Fabricator
 Climax

 Model
 KM65 / KM3000

 Serial no
 9073

# **Specifications**

Power Options..... Air

### Additional information

Equipment / Functions...... Keyway Length: 6" (152.4 mm), optional 1.25" (31.8 mm)

Keyway Width: 1.25" (31.8 mm)

Shaft Diameter: 0.75 - 10.5" (19.1 - 266.7 mm)

#### Compact & Powerful

- Compact, rugged, portable milling machine for on-site keyway and other milling jobs.
- Self-centering and self-aligning V-base.
- Needs only 1.5 inches (38.1 mm) of shaft for clamping.
- Clamps on shafts up to 10.5 inches (266.7 mm) diameter with optional chain clamp.
- Slotted V-base allows you to cut right to the end of the shaft.

# Efficient Operations with High Quality Components

- Vertical and horizontal travel via hand crank.
- Dovetail ways for accurate cutting action.
- Standard Weldon-type spindle accepts 5/8 inch end mills, or 16 mm shank end mills on metric machines.
- Precision Acme thread leadscrew with roller thrust bearings.
- Zeroing-type vertical adjustment dial calibrated to control cutter depth in 0.001 inch (0.1 mm) increments.
- Sealed aluminum alloy gear box permits operation at any angle.
- Precision ground quill housing ensures smooth operation.