Unit no. MM-011

IKM Testing AS



MILLING MACHINE

Dimensions

Length(mm).....: 1500 Width(mm).....: 720 Height(mm).....: 770
Weight - (kg).....: 320

Area of use / certification

Onshore/offshore.....: Offshore

Type

Description.....: Portable mill
Fabricator.....: Climax
Model.....: PM2000
Serial no.....: 9075

Specifications

Power Options.....: Air
Max X-Axis Travel (mm).....: 508.0
Max Y-Axis Travel (mm).....: 203.0
Max Vertical Travel.....: 76.0
Spindle size.....: 0,75" (20mm)

Additional information

Equipment / Functions.....:

Climax's PM Series 3-axis portable milling machinesprovide precise and versatile on-the-job millingcapabilities. They are designed to be attached eitherto the work piece or to a fabricated frame beside it.Downtime savings will pay for the machine in ashort time.
- All gears and drives are permanently lubricatedand sealed to allow operation in any position.
- Precision machined dovetail ways and adjustablegibs provide smooth accurate travel

- The vertical adjusting screw is calibrated foraccurate adjustments and has a locking nut forzeroing.
- Power is delivered by a triple gear reductionpower head with in-line electronic speed controlproviding spindle speeds from 280 to 525 rpm.
- Spindle accepts standard 3/4" Weldon-type shankcutting tools. A 20 mm spindle is available formetric applications