



HIGH PRESSURE TEST PLUG - ELBOW

Dimensions

Equipment Weight - (kg).....: 100
Lifting/ Transportation.....: Transportation on pallet

Type

Item type.....: Testplug for Elbow / Bend
Fabricator.....: Curtiss Wright
Model.....: GTLBO-14P10

Flow / Pressure / Volume

P-max (bar).....: 231 P-max (PSI).....: 3350
Nominal Pipe Size (Inches).....: 14.00
Nominal Pipe Schedule.....: 10
Plug Outside Ø (mm).....: 335.5
Range of use - Minimum (Ø mm).....: 338.3
Range of use - Max recom.(Ø mm): 344.4
Plug Length (mm).....: 378

Additional information

Equipment / Functions.....: Installation:
Normal Installation Torque : 244 Nm
Maximum Installation Torque : 441 Nm

Eliminate welding on end caps/pups with GripTight Elbow Plug. Designed for testing piping, spools and pipe systems terminating in long radius elbows.

Features

- Orientation Free Installation - no need to align with elbow
- Patented Dual-Serrated GripTight MAX® gripper design
- Patented Floating, Self-Aligning grippers & seal
- Easy Installation - No welding or hot work required
- Ideal for horizontal & vertical applications
- Fits any long radius elbows
- Self-gripping design uses test pressure to increase holding power
- Saves significant time vs. welded-on end cap/pup procedures