



## HIGH PRESSURE TEST PLUG - ELBOW

### Dimensions

Equipment Weight - (kg).....: 16  
Lifting/ Transportation.....: Transportation on pallet

### Construction year

Built.....: 2019

### Type

Item type.....: Testplug for Elbow / Bend  
Fabricator.....: Curtiss Wright  
Model.....: GTLBO-6P80

### Flow / Pressure / Volume

P-max (bar).....: 231                      P-max (PSI).....: 3350  
Nominal Pipe Size (Inches).....: 8.00  
Nominal Pipe Schedule.....: 80 / XS  
Plug Outside Ø (mm).....: 138.7  
Range of use - Minimum (Ø mm).....: 141.5  
Range of use - Max recom.(Ø mm): 145.0  
Plug Length (mm).....: 241

### Additional information

Equipment / Functions.....: Installation:  
Normal Installation Torque : 61 Nm  
Maximum Installation Torque : 75 Nm

Eliminate welding on end caps/pups with GripTight Elbow Plug. Designed for testing piping, spools and pipe systems terminating in long radius elbows.

#### Features

- Orientation Free Installation - no need to align with elbow
- Patented Dual-Serrated GripTight MAX® gripper design
- Patented Floating, Self-Aligning grippers & seal
- Easy Installation - No welding or hot work required
- Ideal for horizontal & vertical applications
- Fits any long radius elbows
- Self-gripping design uses test pressure to increase holding power
- Saves significant time vs. welded-on end cap/pup procedures