



## **DIAPHRAGM PUMP**

### **Dimensions**

Length(mm).....: 645                                  Width(mm).....: 490                                  Height(mm).....: 770  
Weight (kg).....: 65  
Lifting/ Transportation.....: Mounted in Frame. Transportation on pallet

### **Construction year**

Built.....: 2019

### **Area of use / certification**

Onshore/offshore.....: Offshore  
Standard.....: EX/Atex, CE, Norsok, Zone 1

### **Type**

Fabricator.....: RAASM  
Model.....: AAB-2-T-550  
Serial no.....: 01700007-2018 (Art no. 3C6/50111 TTP)

### **Flow / Pressure / Volume**

Q-max (l/min).....: 550  
P-max (bar).....: 8                                  P-max (PSI).....: 115  
Flowrate1.....: 500 ltr/min @ 1 bar  
Flowrate2.....: 320 ltr/min @ 4 bar  
Flowrate3.....: 100 ltr/min @ 7 bar  
Max temp. (GrC).....: 100

### **Connections**

Inlet connection.....: 2" Camlock Male  
Outlet connection.....: 2" Camlock Female  
Air connection.....: 1" offshore claw coupling  
Air supply (P@Q).....: Max 6,7 bar

### **Additional information**

Equipment / Functions.....: Max suction, dry : 5,0 metres  
  
Pressure regulator on airtupply to regulate flow / pressure.  
Pump material Aluminium